

(Low-Temp.) Reciprocal Shaker Water Bath

Features

- Accurate temperature control
- Shaking speed is stable and smooth
- With drainage stopcock for easy cleaning
- Supplied with one set of clamps
- PID controlled speed and temperature with LED digital display
- Made with SUS 304 stainless steel body with powder coating
- Gable cover and tube rack are sold separately for your option



▲ BT-350 ▲ BT-150



▲ BT-680

Specifications

Model No.	BT-150D	BT-150RD	BT-350D	BT-350RD	BT-680D
Temp. Range	Ambient +5°C~100°C	0~100°C	Ambient +5°C~100°C	0~100°C	Ambient +5°C~100°C
Temp. Control	PID				
Temp. Display	LED				
Temp. Accuracy	±0.1°C				
Refrigerator	N/A	1/4 HP	N/A	1/4 HP	N/A
Shaking Speed	20~200				
Shaking Width	0.5"~1.5" (Adjustable)				
Volume	22 L		38 L		50 L
Heater	1200 W	1200 W	1600 W	1600 W	1200 W
Shaking Plate	300 x 240 mm	300 x 250 mm	400 x 300 mm	400 x 300 mm	470 x 320 mm
Inside Dimension (WxDxH)	500 x 300 x 150 mm	500 x 300 x 150 mm	610 x 350 x 180 mm	610 x 350 x 180 mm	560 x 410 x 220 mm
Outside Dimension (WxDxH)	710 x 350 x 360 mm	710 x 350 x 590 mm	820 x 400 x 390 mm	820 x 400 x 650 mm	720 x 530 x 540 mm

Capacity for flasks

Flask Clamp	125ml	250ml	500ml	1000ml	2000ml	3000ml	5000ml
BT-150(R)D	12	6	4	2	2	1	-
BT-350(R)D	24	15	8	6	2	2	1
BT-680D	24	15	12	6	6	2	1

Power Voltage : 110V/220V 50Hz/60Hz